



**SPECIFICATIONS:
ELECTRICAL SPECIFICATION**

Contact Current Rating: 1.5 Amperes
 Dielectric Withstanding Voltage: AC 500/60ses.r.m.s.
 Insulation Resistance: 1000 Megohm Min. at DC 500V
 Contact Resistance: 30 milliohm Max.
 Operating Temperature: -25°c ___ +105°c

MATERIALS:

Contacts: Brass
 Contacts Plating: See number description
 Insulator: PBT+G.F UL94V-0
 Shell: Steel

PART NO: ZUS B 2 4 Mxx X03 N 1

- 1, USB type
- 2, Performance:
B= solder type
- 3, Sort:
2 = USB A TYPE 2.0
- 4, Contact No. :
4=4PIN
- 5, Contact Type:
M=Male type,Brass
- 6, Contact plating :
See table1
- 7, Shell material :
F: SPCC
C: BRASS
- 8, series number :
02
- 9 , Shell Plating:
N=Plating nickel
- 10 , Color :
1=White
2=Blue
3=Black

Table 1

CODE	Selective Gold	Type
E1	Gold Flash	Tin plated
E2	Gold 3u"	Tin plated
E3	Gold 10u"	Tin plated
E4	Gold 15u"	Tin plated
E5	Gold 30u"	Tin plated

MARK		DISCRIPTION		REVISIONS		DATE		REVISED		APPROVED		unless otherwise specified tolerance: .X±.38, .XX±.25, .XXX±.15,		ANG±2°	
NAME:		USB A TYPE Male Solder-03		Part No:		ZUS B 2 4 Mxx X03 N 1		Customer Part No.(DWG NO)							
DSSD		HUANGLM		DATE		2011-12-01		SCALE:		VIEW:		UNIT:		mm	
CHKD															
APVD															
FSCONN		Dongguan Fishu Electronic Technology Co.,Ltd		Tel:0755-81765247/41		Fax:0769-81765203									